

PRODUCT INFORMATION

HUSTLER

6BTV, 5BTV, 4BTV



HF Vertical Antennas



6-BTV

5-BTV

4-BTV

Spec.	6-BTV	5-BTV	4-BTV
Bands	6	5	4
Coverage	80,40,30,20, 15,10m	80,40,20, 15,10m	40,20,15, 10m
Bandwidth	Full	Full	Full
Bandwidth 80m	100kHz	100kHz	N/A
VSWR	1.15:1	1.15:1	1.15:1
Power	1kW	1kW	1kW
Traps	25.4mm	25.4mm	25.4mm
Tubing	31.75mm	31.75mm	31.75mm
Bracket size	44.45mm	44.45mm	44.45mm
Height (m)	7.3	7.64	6.52
Weight (kg)	7.48	7.7	6.8
Windload	13kg	13kg	12.7kg

Accessories:

4457-1 Spider assembly converts 4-BTV to 5-BTV (needs RM-80S)

30-MTV 30m (10MHz) add-on kit for 4BTV & 5-BTV.

All the Hustler vertical HF antennas can be ground mounted or elevated. If elevated then radials are required. The antennas only need a single line feed with any length of 50 Ohm coax.

With Hustler verticals, you can not only adjust frequency by tubing length, you can actually tune the traps for up to 2MHz shift. Exclusive trap design makes Hustler traps ultra stable and dependable. Large diameter tubing gives full bandwidth on 10m to 40m with VSWR typically better than 1.6:1 at band edges. Using the 6-BTV or 5-BTV on 80m you will achieve around 100kHz bandwidth. Absence of tapered tubing makes this antenna really strong and the thick tube wall adds to their rigidity.

Order As 6-BTV 6-band HF Vertical Antenna

Order As 5-BTV 5-band HF Vertical Antenna

Order As 4-BTV 4-band HF Vertical Antenna

Waters & Stanton PLC, Spa House, 22 Main Road, Hockley, Essex, SS5 4QS, UK.

Tel: 01702-206835 Fax: 01702-205843 Freephone Orders: 08000 73 73 88

E-mail: sales@wsplc.com Web:www.wsplc.com